

## 026 Masking tape “PERFECT EDGE OUTDOOR”


**Application fields:**
**Technical features:**
**Strengths:**
**Tape structure:**

Backing: Japanese washi paper

Adhesive: acrylic clear adhesive

**Characteristics:** 026 is able to ensure high performances when blade-sharp painting works are required. Suitable on all most common surfaces such as hard PVC, glass, aluminum, wood and gypsum walls. 026 well perform in bad weather conditions like humidity, rain or low /high temperature. Especially suitable for a variety of outdoor works allowing easy outdoor removability up to 5 months after application. 026 guarantees the equivalent to 12 weeks UV resistance.

building, DIY

anti UV, painting, indoor, fine line, water resistant, ECO, no residual

- Precise paint edges for outdoor application
- High UV ray resistance
- Ideal in extreme climate conditions
- Compatible with water and solvent base paints
- Suited for multiple surfaces
- No residue
- Removal without breaking and easy to unroll

**Technical information:**

Properties	Spec.	Tolerance	Test Method
Total Weight	83 g/m <sup>2</sup>	± 10 %	ISO 536
Total Thickness	85 µm	± 10 %	AFERA 5006
MD Tensile strength	> 24 N/cm		AFERA 5004
MD Elongation at break	> 3 %		AFERA 5004
Adhesion to steel plate	> 1,2 N/cm		AFERA 5001

**Available colour:**

Light blue

**Removal without residue (not painted):**

5 months (outdoor)

**Temperature application range:**

-10 °C &gt; +40 °C

**UV light resistance:**

500 h - Atlas Sunset XLS+ (II)

**Storage details:**

- We recommend a storage temperature between 15 and 25 °C
- The product should not be directly exposed to heat or humidity
- The product should be conditioned to room temperature before use

**Shelf life:**

12 months when stored in original carton at 23 °C and max. 50 % relative humidity

**Remark:**

Above figures are for reference and cannot be treated as warranties. Customers are advised to test the material to determine the suitability against intended applications

### IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.