

# 028 Masking tape "PERFECT EDGE"



## Tape structure:

Backing: Japanese washi paper Adhesive: acrylic clear adhesive

# **Characteristics:**

028 is able to ensure high performances when blade-sharp painting works are required. Suitable on almost all common surfaces and designed for indoor and outdoor application. Especially suited for a variety of paint works allowing easy removability without adhesive residual after application. 028 is the perfect tool for outdoor application guarantees one month (non painted).

Application fields:

building, DIY

**Technical features:** 

anti UV, painting, indoor, fine line, water resistant, ECO, no residual

Strengths:

- Precise paint edges
- Compatible with water and solvent base paints
- Suited for multiple surfaces
- No residue
- · Removal without breaking and easy to unroll

#### Technical information:

Properties	Spec.	Tolerance	Test Method
Total Weight Total Thickness MD Tensile strength MD Elongation at break	83 g/m2 85 µm > 24 N/cm > 3 %	± 10% ± 10%	ISO 536 AFERA 5006 AFERA 5004 AFERA 5004
Adhesion to steel plate Removal without residue (not painted) UV light resistance	> 1,1 N/cm 5 months (outdoor 170 h	.,	AFERA 5001  ) untest XLS+ (II)

Available colour:

yellow

Storage details:

- We recommend a storage temperature between 15 and 25 °C
- The product should not be directly exposed to heat or humidity
- The product should be conditioned to room temperature before use

Shelf life:

12 months when stored in original carton at 23 °C and max. 50 % relative humidity

Remark:

Above figures are for reference and cannot be treated as warranties. Customers are advised to test the material to determine the suitability against intended applications

## **IMPORTANT NOTICE TO PURCHASER**

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.

february 2017 www.folsen.eu