



0433948 Packaging tape

Description:

Matt adhesive tape with reinforced adhesive. Particularly recommended to close carton-boxes for storage in unconditioned warehouses with exposure to light. Universal use. Soft and noiseless unwinding. Highly resistant to U.V. light and high and low temperatures. Excellent adhesion characteristics and elasticity makes this tape an ideal choice for insulation of windows in winter.

Construction:

Backing: Matt Bi-oriented polypropylene film 35 μm thickness Adhesive: Waterbased solvent free acrylic adhesive

Technical Details:		Properties	Unit	Values
		Backing thickness	μm	35
		Tensile strength	kg/cm	5.2
		Elongation	%	180
		Total thickness	μm	59
		Adhesion to steel	g/cm	250
	Color: White			
Availability:		48 mm x 66 m, other sizes on request		
Storage:		Where possible the goods should be stored at room temperature, between 14 $^\circ \! ext{C}$		
		and 28 °C. Damp storage conditions should be avoided. The self adhesive tapes are pressure sensitive and must be properly applied to guarantee their good performance.		
R	emark:	Above figures are for reference and Customers are advised to test the m intended applications.		y against

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.